

## Active Optical Module



### Benefits of using *LightABLE* transceivers

- Convert RF signals to optical signals.
- Full duplex optical transceiver with 4 transmit and 4 receive parallel lane, each lane carrying a 12.5 Gbps signal.
- This device is fully qualified for harsh environment applications under MIL-STD 883 shock and vibration.
- Operates under industrial temperature range (-40 °C to 100 °C).
- Data transmission over a distance of 100 m with a bit error rate (BER) better than  $10^{-13}$  and a wide open eye diagram.
- Receiver sensitivity: -12 dBm.
- Small dimensions (L × H × D): 24 mm × 5 mm × 13 mm.
- Low power consumption: 1.8 W with 8 lanes activated.

Meritec, in collaboration with Reflex Photonics, developed a compact and rugged 40 Gbps E/O media convertor meeting ANSI/VITA 76 standard. The module provides a simple solution to upgrade the reach of high speed electrical signals by converting to optical. Error-free transmission at 40 Gbps I/O density over a 100 m was verified in harsh environmental conditions.

The electrical interface uses a size 17 circular shell, while the optical interface is a 12 fiber MT optical ferrule housed in a size 11 circular shell. The length of the media converter is only 7 cm.

### Quote from Meritec

The VITA 76 standard defines a high bandwidth copper I/O connector system that consists of bulkhead-receptacles and cable-end-plugs. The bulkhead receptacle is a connector meeting the MIL-DTL-38999M, Series III circular shell requirements. This new development is about a small form cable end plug which convert electrical RF signals from the copper interface to optical signals using a *LightABLE*™ SR4 transceiver from Reflex Photonics.



### Transceiver used in this application

*LightABLE* LH SR4 embedded transceiver

[www.reflexphotonics.com](http://www.reflexphotonics.com)

For information on Reflex Photonics products, contact:

[sales@reflexphotonics.com](mailto:sales@reflexphotonics.com)

1.514.842.5179 (Montreal) • 1.408.715.1781 (USA)

Reflex Photonics is certified to ISO 9001

All specifications are subject to change without notice. All brands are trademarks or registered trademarks of their respective owners and third party entities. Copyright © 2017 by Reflex Photonics. AOM\_Application\_EN\_201710

THE *Light* on Board® Company

