


REFLEXPHOTONICS®

The most rugged high-performance embedded transceivers.

Reflex products are intrinsically robust making them the ideal choice for the most demanding environment. The sealed optical path guarantees optimum performances over high temperature and humidity ranges. *Light*ABLE based products can be surface mounted and meet the strictest shock and vibration requirements for industrial and military applications.

Reflex Photonics components undergo a severe test program.




Mechanical integrity

Vibration test

- Simple harmonic motion
- 20 Hz to 2000 Hz
- 20 G peak acceleration
- 4 times in each axis
- BER 10^{-12} maintained

Mechanical shock

- Shock pulsed of 500 G
- Pulse duration 0.5 ms
- 5 repetitions
- 6 spatial orientations



Live fiber pull test

- 1 kg weight attached to cable
- 10 min observation time:
BER 10^{-12} maintained

Thermal shock

- 20 cycles
- 0 °C to 100 °C
- Dwell time: 10 min



Environmental testing

Temperature cycling

- Cycling range: -40 °C to 85 °C
- Cycling ramp: 10 °C per min
- 1000 cycles
- Mil-STD-883E Method 103B

Temperature stress

- Cold storage: -57 °C
- Hot storage: 125 °C

Damp heat

- Temperature and humidity test
- MIL-STD-202G, Method 103B
- 500 h at 85 °C and 85 % RH

Reflow test

- Lead (Sn-Pb)
- RoHS



www.reflexphotonics.com

For information on Reflex Photonics products, contact:

sales@reflexphotonics.com

1.514.842.5179 (Montreal) • 1.408.715.1781 (USA)

Reflex Photonics is certified to ISO 9001

All specifications are subject to change without notice. All brands are trademarks or registered trademarks of their respective owners and third party entities. Copyright © 2017 by Reflex Photonics. Rugged_Optics_EN_201710

THE *Light* on Board® Company

